The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Thursday, May 28, 2020** at 12:15 a.m. Eastern Time. Please contact NSF to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: http://info.nsf.org/Certified/DWTU/Listings.asp?Standard=058&Company=3F020&

Note: Certain claims, such as Arsenic (Pentavalent) Reduction, appear as active links, allowing you to access additional information regarding the specific contaminants.

NSF/ANSI 58
Reverse Osmosis Drinking Water Treatment Systems

Kouw Pinnq Ent. Co., Ltd. (C.C.K.)

No. 766, Section 4, Jung Ching Road
Taya District, Taichung City
Taiwan
886 4 2560 0828
Visit this company's website (http://www.cckro.com)

Facility : # 1 Taichung City, Taiwan

COMPONENTS: Filter Housings[1]
(V)(WWW)-(XX)(Y)-(ZZ)

[1] Slim housings
(V) - Body color (white, blue, or black)
(WWW) - Model (892, 893, 894, 889, 905, 913)
(XX) - Slim cap color/Style: BKR (black), WR (white), BR (blue), BKF (black flat), WF (white flat), BF (blue flat)
(Y) - Slim cap port size: 1/4", 3/8", or 1/2" (905 is approved for 1/4" and 3/8" only)
Standard housings
(V) - Standard housings: Body color (white, blue, or black)
(WWW) - Model (890, 891, 910)
(XX) - Standard cap color/Style: BKR (black), WR (white)
(Y) - Standard cap port size: 3/8", 1/2" , 3/4"
(ZZ) - Standard Pressure Relief Button - PR
Big Flow housings
(V) - Big flow housings: Body color (white, blue, or black)
(WWW) - Model (907, 908, 909)
(XX) - Big flow cap color/Style: BK (Black), W (White)
(Y) - Big flow cap port size: 3/4, 1, 1-1/2, 1-1/4
(ZZ) - Big flow pressure relief button: - PR

COMPONENTS: Membrane Pressure Vessels[2]

MH-35DW
MH-35SW
MH-35SW-EZ

[2] Certified for material and structural requirements only.

COMPONENTS: Storage Tanks, Low Pressure[2]

TK-3200[3]
TK-3500[3]
TK-3600
TK-4000[3]
TK-4200[3]

[2] Certified for material and structural requirements only.
[3] As of 1/24/17.

COMPONENTS: Valves, Automatic Shut-off[2]

SV-A-14W-EZ

[2] Certified for material and structural requirements only.

Facility : # 2 Taichung City, Taiwan

COMPONENTS: Tubing[1] [2]

TU-2B
TU-2BK
TU-2G
TU-2O
TU-2R
TU-2W
TU-2Y
TU-3B
TU-3BK
TU-3G
TU-3O
TU-3R
TU-3W
TU-3Y
TU-4B
TU-4W

[1] Certified for material and structural requirements only.
[2] The tubing is sold in coils of 500 ft. or up to defined length. However, Listed tubing has the following length restrictions and must be cut to meet the following restrictions:

TU-2W (0.25" OD) - maximum length of 68"
TU-3W (0.375" OD) - maximum length of 40"
TU-2Y (0.25" OD) - maximum length of 68"
TU-3Y (0.375" OD) - maximum length of 40"

Number of matching Manufacturers is 1
Number of matching Products is 26
Processing time was 0 seconds